

DATASHEET

STCS

evo500



Reference of the product

14-01-0016

Technology

 Infrared


> Media for this machine

The STCS-evo500 is a machine for processing heat shrink tubes, based on infrared resistors.

It's designed for workbench applications and can process one part at a time.

It has built-in communication with ultrasonic welding machines and several operating modes.

It can be supplied with end splice tool with cooling that doesn't have to be removed when working with normal splices.



Holding system that preserves the integrity of the cable, ensuring its immovability during the entire process



Quartz infrared oven that allows higher temperatures



External connection for communication with ultrasonic welding machines, barcode reader or PC programming using Excel™ files



Built-in air treatment unit that provides steady regulation and increase life time of pneumatic components



MECALBI
Engineering Solutions, Lda.
Portugal - USA - México
www.mecalbi.com
www.youtube.com/mecalbi

MECALBI Operations Center Portugal
Zona Industrial de Castelo Branco, Rua J Lote N14, Módulo A
6000-459 Castelo Branco - Portugal
T. +351 272 325 264
E. comercial@mecalbi.com

Centro de Operaciones MECALBI México
Avenida Reforma, #3131 - 5C, Colonia Reforma,
CP. 32380 Cd. Juárez - Chihuahua, México
T. +52 (1) 656 611 6477
E. sales.mexico@mecalbi.mx

MECALBI USA, LLC
12709 Tierra Jezrel Lane,
El Paso, TX 79938, USA
E. sales.usa@mecalbi.com

Technical Data

WORKING TEMPERATURE

Minimum	300 [°C]
Maximum	550 [°C]

DIMENSIONS

Length	496 [mm]
Width	293 [mm]
Height	255 [mm]
Weight	16,5 [kg]

POWER SUPPLY/CONSUMPTION

Supply	230 [V] @ 50Hz
Consumption	250 [mA] to 3 [A] (Max.700W)

CONNECTIONS

Compressed Air	Quick Hold Socket – Ø 8 mm
Air Pressure	Min. 5 Bar; Max. 8 Bar; Rec. 6 Bar
Electrical Grid	1 IEC Standard Male Socket (Detachable Power Supply Cord)

Barcode Reader	DB9 Male
Programming	Membrane Keyboard, Barcode Reader, External Device
Interface	LCD 16x2, Buzzer and LED

SHRINKING CHAMBER

Shrinking Chamber	Ø32 x 77 [mm]
Cable Length [Min]	230 [mm]
Shrinking Tube Diameter [Max]	210 [mm]
Shrinking Tube Length [Max]	75 [mm]

CALIBRATION

Calibration Probe	ref.: 06-01-0158
-------------------	------------------

Features

- Adjustable parameters: process temperature, shrinking time, etc;
- Two different operating modes: M1 with temperature control and shrinking time; and M2 mode with pre-programmed references (100 in total, each having from 1 to 40 shrinking times);
- The pre-programming of references can be done manually or using a PC with STCS-RCT software (reads Excel™ files);
- The selection of references can be done automatically using a barcode reader or manually using either the rotating knob or the keyboard;
- Use of labels and information about additional glue for each shrinking time inside a reference;
- Manual and automatic calibration (single cycle);
- Programming mode password protected;
- Special maintenance mode;
- Cycle and time counter;
- Communication with ultrasonic welding machines;
- Air fault detection;
- Interchangeable system language, including: English, Portuguese, French and Spanish (others on demand);
- Easier maintenance: individual covers to access components;
- Larger fan that reduces the machine's body temperature.


Options



- **End splice tool**
Ref: 26-23-0010



- **CAN tool (normal splice)**
Ref: 26-23-0014



- **CAN tool (end splice)**
Ref: 26-23-0013

- **Ring terminal tool**
Ref: 26-23-0021
- **Cooling system**
Ref: 06-01-0132